


articoli di fissaggio > rivetti a strappo per applicazioni speciali > rivetti a strappo per applicazioni speciali

Rivetti multistadi in alluminio AlMg 2

A testa cilindrica



		d	L	D	A		
Kg	Kg					mm	mm min * max
90 (882 N)	110 (1078 N)	3.2	8	6.5	1	3.4	0.8 Æ 5
90 (882 N)	110 (1078 N)	3.2	9.5	6.5	1	3.4	2 Æ 6.5

		d	L	D	A		
90 (882 N)	110 (1078 N)	3.2	11.5	6.5	1	3.4	4 Æ 8
125 (1225 N)	170 (1666 N)	4	10	8	1.3	4.2	1.2 Æ 6.5
125 (1225 N)	170 (1666 N)	4	13	8	1.3	4.2	4 Æ 9.5
125 (1225 N)	170 (1666 N)	4	17	8	1.3	4.2	8 Æ 13.5
165 (1617 N)	230 (2254 N)	4.8	11	10	1.5	5.1	1.3 Æ 6.5
165 (1617 N)	230 (2254 N)	4.8	15	10	1.5	5.1	4.8 Æ 11.1
165 (1617 N)	230 (2254 N)	4.8	17	10	1.5	5.1	5.5 Æ 12
165 (1617 N)	230 (2254 N)	4.8	25	10	1.5	5.1	12.7 Æ 21