


articoli di fissaggio > inserti filettati > inserti filettati

Inserti filettati a testa cilindrica in lega di alluminio



Codice Nr.	d 6H	D 0 -01	B max	S	L	r min Å· max	 ± 0,05	 mm
M 3 FTT/C	M 3	4.9	8	0.8	9	4.2 Å· 2.6	5	0.3 Å· 1.8
M 3 FTT /L	M 3	4.9	8	0.8	10.5	4.2 Å· 2.6	5	1.8 Å· 3
M 4 FTT/C	M 4	5.9	9	1	11	5.5 Å· 6	6	0.3 Å· 2.5
M 4 FTT/L	M 4	5.9	9	1	13	5.5 Å· 6	6	2.5 Å· 4
M 5 FTT/C	M 5	6.9	10	1.2	13	7.2 Å· 7.7	7	0.5 Å· 3
M 5 FTT/L	M 5	6.9	10	1.2	15.5	7.2 Å· 7.7	7	3 Å· 5
M 6 FTT/C	M 6	8.9	12	1.5	14.5	7.6 Å· 8.2	9	0.5 Å· 2.3
M 6 FTT/M	M 6	8.9	12	1.5	16	7.6 Å· 8.2	9	2.3 Å· 4
M 6 FTT/L	M 6	8.9	12	1.5	17.5	7.6 Å· 8.2	9	4 Å· 6
M 8 FTT/C	M 8	10.9	15	1.5	17.5	9.5 Å· 10.1	11	0.8 Å· 3.5
M 8 FTT/L	M 8	10.9	15	1.5	20	9.5 Å· 10.1	11	3.5 Å· 6
M 10 FTT/C	M 10	11.9	16	1.7	19	10.7 Å· 11.5	12	1 Å· 3.5
M 10 FTT/L	M 10	11.9	16	1.7	22	10.7 Å· 11.5	12	3.5 Å· 6
M 10 FTT/C	M 10	12.9	17	1.7	21	12.5 Å· 13.5	13	1 Å· 3.5
M 10 FTT/L	M 10	12.9	17	1.7	24	12.5 Å· 13.5	13	3.5 Å· 6

A richiesta inserti filettati in lega di alluminio anodizzati nei colori: argento, bronzo, nero, testa di moro.
 Inserti in acciaio bruniti, ramati, ottonati.