

sette elettrico > fascette stringicavo > fascette stringicavo

Fascette stringicavo



Codice Nr.	L	H	Tenuta minima (kg)	Max Å, di serraggio
4201	75	2.2	6	15
4203	98	2.5	8.16	21
4205	135	2.6	8.16	32
4206	60	2.6	8.16	40
4207	200	2.6	8.16	52
4209	140	3.6	13	35
4214	200	3.6	13	50
4210	290	3.6	13	80
4212	120	4.5	20	24
4211	160	4.5	20	40
4213	178	4.8	22	45
4215	200	4.8	22	50
4217	290	4.8	22	79
4218	390	4.8	22	106
4219	360	4.8	22	103
4220	430	4.8	22	115

sette elettrico > fascette stringicavo > fascette stringicavo


Fascette per fissaggio a pannello



Codice Nr.	L	H	Å, Foro	Spessore pannello	Tenuta minima (kg)	Max Å, di serraggio
42155-M	150	3.5	5.2	2.8	13	38
42205-M	200	4.8	6.3	3.6	22	50

sette elettrico > fascette stringicavo > fascette stringicavo

Fascetta ad occhiello



Codice Nr.	L	H	Å, Occhiello	Tenuta minima (kg)	Max. Å, di serraggio
42150-I	150	3.6	4.5	13	32
42200-S	200	4.8	4.5	20	54
42200-H	200	7.8	6.5	55	50
42300-H	300	7.8	6.5	55	75
42380-H	380	7.8	6.5	55	104